



Smart Network Access System

Portable/Standalone Chassis



- One (1) Hot-Swappable Module Slot
- Dual AC or DC - 48vdc power supplies
- Local or remote configuration
- Modular design provides the ability to make updating your infrastructure quick, easy and inexpensive.
- Easily installs anywhere in the network infrastructure.
- Supports Copper and Fiber Environments
- Allows secure and easy access for all of your network appliances

Product Specifications

Size Dimensions (W x H x D)	5.8 in x 1.8 in x 7.5 in / 14.7 cm x 4.6 cm x 19.1 cm
Weight	1.4 lbs / 0.6 kg
Operating Temperature	0°C to +40°C / +32°F to +104°F
Operating Relative Humidity	90 % non-condensing
Storage Temperature	-20°C to +70°C / -4°F to +158°F
Voltage (AC/DC)	85V–264V AC / 7v–60 v DC
Current (nominal)	1.25 @ 12VDC
Frequency	47–63 Hz
Maximum Power Consumption	7 Watts

Ordering Information:

SNAC0AC— Portable Modular Chassis, 1 Hot-swappable Module Slot, Dual AC Power Supplies

SNAC0DC— Portable Modular Chassis, 1 Hot-swappable Module Slot, Dual DC—48vdc Power Supplies

Headquarters

12B Southview Park
Caversham, Reading, RG4 5AF
0118 954 3210
Sales@NetworkCritical.com

WWW.NETWORKCRITICAL.COM

Americas Office

3675 Harlem Road
Buffalo, NY 14215
(716) 558-7280
Sales-US@NetworkCritical.com